UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/779,950	02/13/2004	Sanjay Kaniyar	13768.491	9155

22913   7590   02/13/2008

WORKMAN NYDEGGER
60 EAST SOUTH TEMPLE
1000 EAGLE GATE TOWER
SALT LAKE CITY, UT 84111

EXAMINER
MCNALLY, MICHAEL S

ART UNIT	PAPER NUMBER
2136	

MAIL DATE	DELIVERY MODE
02/13/2008	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)
Office Action Summary	10/779,950	KANIYAR ET AL.
	Examiner	Art Unit
	Michael S. McNally	2136

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE <u>3</u> MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1)☒ Responsive to communication(s) filed on <u>13 February 2004</u>.
2a)☐ This action is **FINAL**.   2b)☒ This action is non-final.
3)☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4)☒ Claim(s) <u>1-40</u> is/are pending in the application.
    4a) Of the above claim(s) _____ is/are withdrawn from consideration.
5)☐ Claim(s) _____ is/are allowed.
6)☒ Claim(s) <u>1-40</u> is/are rejected.
7)☐ Claim(s) _____ is/are objected to.
8)☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9)☐ The specification is objected to by the Examiner.
10)☒ The drawing(s) filed on <u>13 February 2004</u> is/are: a)☒ accepted or b)☐ objected to by the Examiner.
    Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
    Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
11)☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12)☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
    a)☐ All   b)☐ Some * c)☐ None of:
        1.☐ Certified copies of the priority documents have been received.
        2.☐ Certified copies of the priority documents have been received in Application No. _____.
        3.☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
    * See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1) ☒ Notice of References Cited (PTO-892)
2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
3) ☒ Information Disclosure Statement(s) (PTO/SB/08)
    Paper No(s)/Mail Date <u>20040213, 20050329</u>.

4) ☐ Interview Summary (PTO-413)
    Paper No(s)/Mail Date. _____ .
5) ☐ Notice of Informal Patent Application
6) ☐ Other: _____.

DETAILED ACTION

1.   Claims 1-40 are presented for examination.

2.   The claims and only the claims form the metes and bounds of the invention. "Office personnel are to give claims their broadest reasonable interpretation in light of the supporting disclosure. In re Morris, 127 F.3d 1048, 1054-55, 44 USPQ2d 1023, 1027-28 (Fed. Cir. 1997). Limitations appearing in the specification but not recited in the claim are not read into the claim. In re Prater, 415 F.2d 1393, 1404-05, 162 USPQ 541, 550-551 (CCPA 1969)" (MPEP p 2100-8, c 2, l 45-48; p 2100-9, c 1, l 1-4). The Examiner has full latitude to interpret each claim in the broadest reasonable sense. The Examiner will reference prior art using terminology familiar to one of ordinary skill in the art. Such an approach is broad in concept and can be either explicit or implicit in meaning.

Information Disclosure Statement

3.   The information disclosure statement (IDS) submitted on 13 February 2004 and 29 March 2005 have been considered by the examiner.

Claim Rejections - 35 USC § 102

4.   The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

5.   **Claims 1-2, 4-8, 10-12, 14-18, 20-22, 24-28, 30-32, 34-38 and 40 are rejected**

under 35 U.S.C. 102(b) as being anticipated by Network working Groups, request

for Comments 1948, "Defending against Sequence Number Attacks" by *Bellovin*.

As to **claims 1 and 21**, *Bellovin* teaches: In a local server that receives data from

one or more remote clients over a data transport protocol (*Bellovin:* Page 2, Lines 1-5;

client talking to server using a TCP connection), a method/computer program product of

generating an initial sequence number for use by a remote client when assigning

sequence numbers to one or more data packets to be sent to the local server (*Bellovin*:

Page 3, Lines 22-24), the initial sequence number generated in a manner that prevents

the local server from being attacked while maintaining reliable data transfer (*Bellovin:*

Page 4, Lines 1-3; Compute F in such a way that it cannot be guessed by discovering

other initial sequence numbers), the method comprising the acts of:

generating a random input key using arbitrary information maintained secret by

the local server (*Bellovin*: Page 4, Lines 3-13; F value generated based on a per-host

secret);

receiving a connection identifier key that includes connection information for at

least the remote client (*Bellovin*: Page 3, Lines 37-38; 4-tupe of <localhost, localport,

remotehost, remoteport> used to compute F);

securely initializing a hash function with at least a portion of the random input key

and at least a portion of the connection identifier key for determining an intermediate

value of an initial sequence number (*Bellovin*: Page 4, Lines 3-5; F is a hash of

connection id and secret data);

creating a monotonically increasing counter (*Bellovin*: Page 2, Lines 25-27,

Counter M) for ensuring that a same connection identifier does not have data collisions

from competing sequence numbers within a predetermined period of time (*Bellovin*:

Page 3, Lines 23-25; prevent stale packets from being accepted by new incarnation f

same connection), and for ensuring randomness of the initial sequence number on a

per connection basis for preventing attacks on the local server (*Bellovin*: Page 2, Lines

25-32, insufficient randomness leads to attacks);

incrementing the counter a fixed value based on a passage of a predetermined

time period (*Bellovin*: Page 2, Lines 26-30, M incremented either 1 every 4 microsecond

in one implementation or by a constant per second in another);

incrementing the counter a variable amount depending upon a rate of

connections with the local server, wherein if the rate of connections is beyond a

threshold value the variable increment is based on an elapsed time, otherwise the

variable increment is based on each connection established with the local server

(*Bellovin:* Page 2, Lines 28-30; under Berkeley implementation, the counter is

implemented by a constant for every connection. The threshold value for Berkeley

would be when the rate of the number of connections cannot increase due to system

considerations, at that point the counter would be applied on an elapsed time, i.e. How

long it takes to establish a connection, rather than on a per connection basis); and

combining the intermediate value, the fixed value and the variable amount for

generating the initial sequence number (*Bellovin*: Page 3-4; ISN computed using M + F

(localhost, localport, remotehost, remoteport), where M = fixed + variable from above

and F is the intermediate value from the 4-tuple as calculated above)

As to **claims 11 and 31**, *Bellovin* teaches: In a local server that receives data

from one or more remote clients over a data transport protocol (*Bellovin:* Page 2, Lines

1-5; client talking to server using a TCP connection), a method/computer program

product of generating an initial sequence number for use by a remote client when

assigning sequence numbers to one or more data packets to be sent to the local server

(*Bellovin*: Page 3, Lines 22-24), the initial sequence number generated in a manner that

prevents the local server from being attacked while maintaining reliable data transfer

(*Bellovin:* Page 4, Lines 1-3; Compute F in such a way that it cannot be guessed by

discovering other initial sequence numbers), the method comprising the acts of:

determining an intermediate value of an initial sequence number by hashing a

random input key and a connection identifier key, which includes connection information

for at least the remote client, the random input key being generated using arbitrary

information maintained secret by the local server (*Bellovin*: Page 4, Lines 3-5; F is a

hash of connection id and secret data from server);

ensuring that a same connection identifier does not have data collisions from

competing sequence numbers within a predetermined period of time (*Bellovin*: Page 3,

Lines 23-25; prevent stale packets from being accepted by new incarnation f same

connection), and ensuring randomness of the initial sequence number on a per

connection basis for preventing attacks on the local server by monotonically

incrementing a counter both a fixed value based on a passage of a predetermined time

period and a variable amount depending upon a rate of connections with the local

server (*Bellovin*: Page 3, Lines 25-32; one constant per time interval and a second per

connection), wherein if the rate of connections is beyond a threshold value the variable

increment is based on an elapsed time, otherwise the variable increment is based on

each connection established with the local server (*Bellovin:* Page 2, Lines 28-30; under

Berkeley implementation, the counter is implemented by a constant for every

connection. The threshold value for Berkeley would be when the rate of the number of

connections cannot increase due to system considerations, at that point the counter

would be applied on an elapsed time, i.e. How long it takes to establish a connection,

rather than on a per connection basis); and

generating the initial sequence number by combining the intermediate value, the

fixed value and the variable amount. (*Bellovin*: Page 3-4; ISN computed using M + F

(localhost, localport, remotehost, remoteport), where M = fixed + variable from above

and F is the intermediate value from the 4-tuple as calculated above).

As to **claims 2, 12, 22 and 32**, *Bellovin* further teaches wherein if the rate of

connections is below the threshold value, the fixed value is further incremented based

on each connection established with the local server (*Bellovin*: Page 2, Lines 25-32).

As to **claims 4, 14, 24 and 34**, *Bellovin* further teaches wherein the connection

identifier key further includes connection information for one or more of the local server

port, local server routing address, remote port and remote routing address (*Bellovin*:

Page 3, Lines 37-38; 4-tuple of <localhost, localport, remotehost, remoteport> used to

compute F).

As to **claims 5, 15, 25 and 35**, *Bellovin* further teaches wherein the data

transport protocol is Transmission Control Protocol (*Bellovin*: Page 2, Lines 1-3), and

wherein the local and remote routing addresses are Internet Protocol addresses

(*Bellovin*: Page 4, Lines 9, 16).

As to **claims 6, 16, 26 and 36**, *Bellovin* further teaches wherein at least a second

connection is made between the local server and a second remote client (*Bellovin*:

Page 3, Lines 35-42), and wherein the method further including the acts of:

receiving a second connection identifier key that includes connection information

for at least the second remote client (*Bellovin*: Page 3, Lines 35-42);

securely initializing the hash function with at least a portion of the random input

key and at least a portion of the second connection identifier key for determining a

second intermediate value of a second initial sequence number (*Bellovin*: Page 4, Lines

3-5; F is a hash of connection id and secret data);

based on at least a portion of the second connection identifier key (*Bellovin*:

Page 3, Lines 35-42, each 4-tuple gets its own number space), creating a second

monotonically increasing counter (*Bellovin*: Page 2, Lines 25-27, Counter M) for

ensuring that a same connection identifier does not have data collisions from competing

sequence numbers within a predetermined period of time (*Bellovin*: Page 3, Lines 23-

25; prevent stale packets from being accepted by new incarnation f same connection),

and for ensuring randomness of the initial sequence number on a per connection basis

for preventing attacks on the local server (*Bellovin*: Page 2, Lines 25-32, insufficient

randomness leads to attacks);

incrementing the second counter the fixed value based on the passage of the
predetermined time period (*Bellovin*: Page 2, Lines 26-30, M incremented either 1 every
4 microsecond in one implementation or by a constant per second in another);

incrementing the second counter a second variable amount depending upon a
rate of connections with the local server and for those connections associated with the
second counter, wherein if the rate of connections with the local server and for those
connections associated with the second counter is beyond a threshold value the
variable increment is based on an elapsed time, otherwise the variable increment is
based on each connection established with the local server and associated with the
second counter (*Bellovin:* Page 2, Lines 28-30; under Berkeley implementation, the
counter is implemented by a constant for every connection. The threshold value for
Berkeley would be when the rate of the number of connections cannot increase due to
system considerations, at that point the counter would be applied on an elapsed time,
i.e. How long it takes to establish a connection, rather than on a per connection basis);
and

combining the second intermediate value, the fixed value and the second
variable amount for generating the second initial sequence number (*Bellovin*: Page 3-4;
ISN computed using M + F(localhost, localport, remotehost, remoteport), where M =
fixed + variable from above and F is the intermediate value from the 4-tuple as
calculated above).

As to **claims 7, 17, 27 and 37**, *Bellovin* further teaches wherein the arbitrary
information maintained as a secret by the local server is based on timing, state

conditions for the local server, or both, at boot up time of the local server, which include

one or more of a time of day, a day of month, a month, a year, a local server hard drive

head position, and whether input was detected by hardware of the local server (*Bellovin*:

Page 4, Lines 7-9; Boot time of the machine used in secret data, which necessarily

includes at least one of the time of day, month or year if not all).

As to **claims 8, 18, 28 and 38**, *Bellovin* further teaches wherein the combining of

the intermediate value, the fixed value and the variable amount is a mathematical

operation or function (*Bellovin*: Page 3, Line 50 ISN = M + F (addition)).

As to **claims 10, 20, 30 and 40**, *Bellovin* further teaches , wherein the

monotonically increasing counter is shared by at least two connections at the same time

(*Bellovin*: Page 2, Lines 28-30, counter used by all connections to server, as each new

connection increments it).

Claim Rejections - 35 USC § 103

6.   The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all

obviousness rejections set forth in this Office action:

> (a) A patent may not be obtained though the invention is not identically disclosed or described as set
> forth in section 102 of this title, if the differences between the subject matter sought to be patented and
> the prior art are such that the subject matter as a whole would have been obvious at the time the
> invention was made to a person having ordinary skill in the art to which said subject matter pertains.
> Patentability shall not be negatived by the manner in which the invention was made.

7.   The factual inquiries set forth in *Graham* **v.** *John Deere Co.*, 383 U.S. 1, 148

USPQ 459 (1966), that are applied for establishing a background for determining

obviousness under 35 U.S.C. 103(a) are summarized as follows:

1.   Determining the scope and contents of the prior art.

      2.   Ascertaining the differences between the prior art and the claims at issue.

      3.   Resolving the level of ordinary skill in the pertinent art.

      4.   Considering objective evidence present in the application indicating obviousness or nonobviousness.

8.   Claims 3 and 33 are rejected under 35 U.S.C. 103(a) as being unpatentable over Network working Groups, request for Comments 1948, "Defending against Sequence Number Attacks" by *Bellovin* in view of U.S. Patent Application Publication No. 2002/0187788 to *McKay*.

As to **claims 3 and 33**, *Bellovin* discloses all recited limitations of claims 1 and 31 from which claims 3 and 33 depend respectively.

Bellovin does not expressly disclose wherein based on the fixed value, if a remote client's data transfer rate while connected to the local server is less than a specified byte rate then the connection identifier used by the remote client the is allowed immediate re-connection to the local server after the remote client disconnects.

McKay discloses wherein based on the fixed value, if a remote client's data transfer rate while connected to the local server is less than a specified byte rate then the connection identifier used by the remote client the is allowed immediate re-connection to the local server after the remote client disconnects (*McKay*: Fig 6; Page 1, Sec 7 and Page 3-4, Sec 27-33; when service degrades below and acceptable level and the user is disconnected, the connection is re-established).

Bellovin and *McKay* are analogous art because they are from the art of networks.

At the time of invention, it would have been obvious to a person of ordinary skill in the art to allow connections without the possibility of collision the ability to reconnect. The rationale would have been to reduce network disruptions (*McKay*: Page 1, Sec 2)

9.   **Claims 9, 19, 29 and 39 are rejected under 35 U.S.C. 103(a) as being unpatentable over Network working Groups, request for Comments 1948, "Defending against Sequence Number Attacks" by *Bellovin* in view of U.S. Patent Application Publication No. 2002/0083175 to *Afek et al.*

As to **claims 9, 19, 29 and 33**, *Bellovin* discloses all recited limitations of claims 1, 11, 20 and 30 from which claims 9, 19, 29 and 39 depend respectively. *Bellovin* additionally discloses wherein if the rate of connections is beyond the threshold value the variable increments up to an amount of 0x000022FB every millisecond (*Bellovin: Page 2, Lines 26-30*),

Bellovin does not expressly disclose otherwise the variable increment is an amount between 16 K and 32 K.

Afek discloses otherwise the variable increment is an amount between 16 K and 32 K (Afek, Fig 4B).

Bellovin and *McKay* are analogous art because they are from the art of networks.

At the time of invention, it would have been obvious to use variable increments depending on threshold values. The rationale would have been that it is obvious to combine these known elements to yield the predictable result of the instant application. *Bellovin* and *Afek* in combination contained all of the elements required for claims 9, 19, 29 and 39, however, the difference being that neither *Bellovin* nor *Afek* combined said elements. One of ordinary skill in the art could have combined the elements present in *Belovin* and *Afek* with the knowledge that in combination, said elements would have

performed the same functions that they did separately.   Furthermore, one of ordinary

skill in the art would have recognized that the results of the combination were

predictable. In fact, for one of ordinary skill in the art of software systems development,

there would have been a reliance on the fact that the results of the combination would

be predictable.

10.   **Claims 13 and 23 are rejected under 35 U.S.C. 103(a) as being unpatentable**

over Network working Groups, request for Comments 1948, "Defending against

Sequence Number Attacks" by *Bellovin* **in view of U.S. Patent Application**

Publication No. 2002/0187788 to *McKay* **and U.S. Patent No. 3,728,535 to** *Dickman*

et al.

As to **claims 13 and 23**, *Bellovin* discloses all recited limitations of claims 11 and

21 from which claims 13 and 23 depend respectively.

Bellovin does not expressly wherein the fixed value is 25.6 K (*Dickman*: Col 7,

Line 8), and wherein if a remote client's data transfer rate while connected to the local

server is less than 256 K then the connection identifier used by the remote client the is

allowed immediate re-connection to the local server after the remote client disconnects

(*McKay*: Fig 6; Page 1, Sec 7 and Page 3-4, Sec 27-33).

Dickman discloses wherein the fixed value is 25.6 K (*Dickman*: Col 7, Line 8).

McKay discloses wherein if a remote client's data transfer rate while connected to

the local server is less than 256 K then the connection identifier used by the remote

client the is allowed immediate re-connection to the local server after the remote client

disconnects (*McKay*: Fig 6; Page 1, Sec 7 and Page 3-4, Sec 27-33).

Bellovin, *McKay* and *Dickman* are analogous art because they are from the art of

networks.

At the time of invention, it would have been obvious to a person of ordinary skill

in the art to allow connections operating at various connection speeds without the

possibility of collision the ability to reconnect. The rationale would have been to reduce

network disruptions (*McKay*: Page 1, Sec 2).

Prior Art

11.   The prior art made of record and not relied upon is considered pertinent to

applicant's disclosure. U.S. Patent Application Publication 2001/0042200 by Lamberton

et al discloses generating Initial Sequence Numbers in such a way as to avoid flooding

attacks (*Lamberton:* Fig 6B).

Conclusion

Any inquiry concerning this communication or earlier communications from the

examiner should be directed to Michael S. McNally whose telephone number is

(571)270-1599. The examiner can normally be reached on Monday through Friday 9:00

- 5:00 EST.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Nasser Moazzami can be reached on (571)272-4195. The fax phone

number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

MSM
7 February 2008

/Nasser G Moazzami/

Supervisory Patent Examiner, Art Unit 2136